

DATA TRANSMISSION SYSTEM AND MOBILE COMMUNICATION SYSTEM

Publication number: JP10174185

Publication date: 1998-06-26

Inventor: SAKAKOSHI KOUJI

Applicant: NIPPON DENKI IDO TSUSHIN KK

Classification:

- international: **H04Q7/38; H04B7/26; H04L12/56; H04Q11/04; H04Q7/38; H04B7/26; H04L12/56; H04Q11/04; (IPC1-7): H04Q11/04; H04Q7/38; H04Q11/04**

- European:

Application number: JP19960326663 19961206

Priority number(s): JP19960326663 19961206

[Report a data error here](#)

Abstract of JP10174185

PROBLEM TO BE SOLVED: To minimize data avoided undesirably due to mismatching between a transmission speed and a buffer capacity and invalid data losing real time performance. **SOLUTION:** A host station 1 designates an outgoing control physical channel structure to a radio base station 3 at the start system operation. The radio base station 3 obtains an optimum buffer capacity C_s according to an equation $C_s = V_s \times T_e$, where V_s is a transmission speed in each function channel depending on a designated control physical channel structure and T_e is a time a reply wait time of a host station 1 from a mobile equipment 5 with some margin. Since the buffer capacity is selected in this way, data invalidated not in time for a reply wait of the host station 1 in a consecutive high load state are aborted before being stored in the buffer. Thus, the data sent to the mobile equipment 5 actually are all validated and then the transmission capability of a radio channel is utilized efficiently.



